



# System FERRO-LUX

## DESCRIPTION

Connection pipe made of sheet steel for connection to stoves and use as a visible element in living rooms, dry operation

## MATERIAL

Steel sheet DC01 (St12)

## FINISHING

Coated with heat-resistant Senotherm paint

Colours:

Black 702.284 or  
cast grey 702.288

On request:

Black-metallic 702.310,  
Light cast grey 800.820

## WALL THICKNESS

2.0 mm

## INSIDE DIAMETER

120 - 200 mm

Others on request

## CONNECTION

Plug-and-socket connection with slip-on connector ends  
Please refer to the respective code for deviations.



## ORDER CODE


The article code for your order results from: System + article code + Ø (e.g.: FERRO1416120)

If you require different colors, please use the following article codes instead of FERRO1.../FERRO-E1.../FERRO-R1... (black):

FERRO2.../FERRO-E2.../FERRO-R2... Black metallic

FERRO4.../FERRO-E4.../FERRO-R4... Light cast gray

FERRO3.../FERRO-E3.../FERRO-R3... cast grey



## APPLICATION AREAS

- Standard fireplaces for solid fuels  
(natural wood, coke, peat, coal\*)

- Stoves

\* except anthracite coal from Ibbenbüren, Germany

## CE MARK NUMBER

0036 CPR 9174 017

## CE CLASSIFICATIONS - DIN EN 1856 - 2

T600 - N1 - D - Vm - L01200 - G400<sup>1</sup>

<sup>1</sup> with radiation protection